

Specifications

Outdoor unit

2WAY (Type ME2)

Model Name		U-8ME2E8	U-10ME2E8	U-12ME2E8	U-14ME2E8	U-16ME2E8
Power source		380 / 400 / 415 V 3N ~ 50 Hz				
Cooling capacity	kW	22.4	28.0	33.5	40.0	45.0
	BTU/h	76,500	95,600	114,300	136,500	153,600
Heating capacity	kW	25.0	31.5	37.5	45.0	50.0
	BTU/h	85,300	107,500	128,000	153,600	170,600
Sound pressure level	dB(A)	54.0	56.0	59.0	60.0	61.0
Sound power level	dB(A)	75.0	77.0	80.0	81.0	82.0
Unit dimensions (H×W×D)	mm	1842×770×1000	1842×770×1000	1842×1180×1000	1842×1180×1000	1842×1180×1000
Net weight	kg	210	210	270	315	315

Model Name		U-18ME2E8	U-20ME2E8
Power source		380 / 400 / 415 V 3N ~ 50 Hz	
Cooling capacity	kW	50.0	56.0
	BTU/h	170,600	191,100
Heating capacity	kW	56.0	63.0
	BTU/h	191,100	215,000
Sound pressure level	dB(A)	59.0	60.0
Sound power level	dB(A)	80.0	81.0
Unit dimensions (H×W×D)	mm	1842×1540×1000	1842×1540×1000
Net weight	kg	375	375

Rated conditions

Cooling : Indoor intake air temp. 27°C DB / 19°C WB. Outdoor intake air temp. 35°C DB.

Heating : Indoor intake air temp. 20°C DB. Outdoor intake air temp. 7°C DB / 6°C WB.