

Specifications

Outdoor unit

Single Split Outdoor Unit (R32)

Model Name		U-36PZH2E5	U-50PZH2E5	U-60PZH2E5
Power source		220 - 230 - 240 V~ 50 Hz		
Cooling capacity	kW	3.6	5.0	6.0
	BTU/h	12,300	17,100	20,500
Heating capacity	kW	4.0	5.6	7.0
	BTU/h	13,600	19,100	23,900
Sound Pressure level (Cooling / Heating)	dB(A)	43 / 44	45 / 48	46 / 49
Sound Power level (Cooling / Heating)	dB(A)	62 / 64	64 / 68	65 / 69
Unit Dimensions (H×W×D)	mm	695×875×320	695×875×320	695×875×320
Net weight	kg	43	43	44

Operation condition temperature range

• Cooling mode : -15°C~46°C DB • Heating mode : -20°C~18°C WB / -20°C~24°C DB

Model Name		U-60PZ2E5	U-71PZ2E5
Power source		220 - 230 - 240 V~ 50 Hz	
Cooling capacity	kW	6.0	7.1
	BTU/h	20,500	24,200
Heating capacity	kW	6.0	7.1
	BTU/h	20,500	24,200
Sound Pressure level (Cooling / Heating)	dB(A)	46 / 48	49 / 49
Sound Power level (Cooling / Heating)	dB(A)	65 / 68	69 / 69
Unit Dimensions (H×W×D)	mm	695×875×320	695×875×320
Net weight	kg	44	44

Operation condition temperature range

• Cooling mode : -10°C~43°C DB • Heating mode : -15°C~18°C WB / -15°C~24°C DB

Rated conditions

Cooling : Indoor intake air temp. 27°C DB / 19°C WB. Outdoor intake air temp. 35°C DB.

Heating : Indoor intake air temp. 20°C DB. Outdoor intake air temp. 7°C DB / 6°C WB.

Corresponding language table

English	Français	Español	Deutsch
Single Split	Bi-bloc simple	Un solo split	Einzel-Split

English	Italiano	Nederlands	Português
Single Split	Split singolo	Enkele splitsing	Single split

English	Ελληνική	Български	Türkçe
Single Split	Απλου συστήματος	Единичен сплит	Tekli Split